



DYNATRON CORPORATION

NEW PRODUCT SPEC SHEET

Part Number: G199

- For Intel® Nehalem Processor, Socket LGA 1356/1366
- Active Cooler For 1U Server
- RoHS Compliant

Overall Specification:


- Dimension: 90.0mm x 90.0mm x 27.8mm
- Weight: 475g \pm 5g
- Material: Copper Heatsink with Skiving Fins
- Captive mounting design
- Back Plate is not included
- Thermal Grease TIG830SP Pre-printed

Blower Specification:




- 7015 Aluminum Blower
- Dimension: 70mm x 70mm x 16mm
- Rated Speed:
 - At Duty Cycle 20%: 1100 \pm 10%RPM
 - At Duty Cycle 50%: 2600 \pm 10%RPM
 - At Duty Cycle 100%: 6000 \pm 10%RPM
- Bearing: 2X Ball
- Rated Voltage: 12V
- Input Power:
 - At Duty Cycle 20%: 0.6W
 - At Duty Cycle 50%: 1.2W
 - At Duty Cycle 100%: 8.76W
- Maximum Airflow:
 - At Duty Cycle 20%: 2.45 CFM
 - At Duty Cycle 50%: 5.80 CFM
 - At Duty Cycle 100%: 14.32 CFM

- Acoustical Noise:
 - At Duty Cycle 20%: 19.1 dBA
 - At Duty Cycle 50%: 34.2 dBA
 - At Duty Cycle 100%: 53.8 dBA
- Lead Wire Pin Out:
 - Pin#1-Black(-)
 - Pin#2- Yellow(+)
 - Pin#3- Green(Tachometer/ Signal Output)
 - Pin#4- Blue (PWM)

Cooler G199, Thermal Performance VS. Blower Acoustical Level Chart :



ITEM#	DESCRIPTION	CHECKER	DATE
01	INITIAL RELEASE	LANG	01/14/2009




	NAME	DATE
DRAWN BY	-	01/14/2009
CHECKED BY	LANG	01/14/2009
ENG. APPROVED		
MFG. APPROVED	-	-


DYNATRON CORPORATION
DYNAEON INDUSTRIAL CO., LTD.

TITLE: CPU COOLER G199
 OVERALL DIMENSION DRAWING

CONFIDENTIAL DOCUMENT

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. MAY OTHERWISE AGREE TO IN WRITING.

VIEW		DWG. No:	REV.
UNITS	MM	DYN-DM-G199	00




Top Motor Technology(HuiZhou)CO.,LTD

FAN TEST PERFORMANCE CURVES

Model	DB127015BH
R.P.M.	6000
Noise	51.4dBA
Date	9/28/2006

P(mmH2O)	P(inH2O)	Q(CMM)	Q(CFM)
0	0	0.371	13.11
8.083	0.318	0.343	12.12
16.386	0.645	0.293	10.35
23.7	0.933	0.235	8.311
32.418	1.276	0.160	5.643
36.895	1.453	0.109	3.834
41.082	1.617	0.056	1.96
46.121	1.816	0	0



TEL:86-0752-3535591
<http://www.dynaeon.com>

FAX:86-0752-3535592
E-MAIL:Sales@dynaeon.com

APPROVED BY:

CHECK BY:

TEST BY:



DYNATRON CORPORATION

Dynaeon Industrial Co., Ltd.

Specification for Approval

Customer:

Model Number: DB127015BU-PWM(70*70*15)

Part Number:

Issued Date: Tuesday January 09, 2007

Customer Approval	
Approval:	Check:

Corporate Headquarters
Dynatron Corporation
 41458 Christy Street,
 Fremont, California 94538,
 U.S.A.
 Tel: 510-498-8888
 Fax: 510-498-8488

Manufactory
Dynaeon Industrial Co., Ltd.
 Ta-Li Management Zone,
 Ching-His, Dongguan,
 CHINA
 Tel: 86-769-8731-3308 (Rep.)
 Fax: 86-769-8731-2296

Los Angeles Office (U.S.A.)
 337 Paseo Sonrisa,
 Walnut, California 91789
 U.S.A.
 Tel: 909-598-2222
 Fax: 909-598-8158

Taipei Office (Taiwan, R.O.C.)
 8F, No. 35, Lane:221,
 Gang Cian Road, Taipei,
 Taiwan, R.O.C.
 Tel: 886-2-2799-5799(Rep.)
 Fax: 886-2-2799-9577

Approval:	Check:	Initiator:
林俊甫 January 09, 2007	余大慶 蔣尙偉 January 09, 2007	汪江濤



DYNATRON CORPORATION

Dynaeon Industrial Co., Ltd.

CONTENTS		Page
1.	SCOPE	3
2.	ELECTRICAL CHARACTERISTICS	3
3.	MECHANICAL CHARACTERISTICS	4
4.	ENVIRONMENTAL	4
5.	PROTECTION	5
6.	ATTACHMENTS	5
	a. Assembly Drawing	6
	b. Product Dimension	7
	c. Electrical specifications for pwm production	8-9



DYNATRON CORPORATION

Dynaeon Industrial Co., Ltd.

1. SCOPE

This specification defines the electrical and mechanical characteristics of the AC / DC Brush less (Sleeve Bearing / 1-Ball Bearing / 2-Balls Bearing) axial flow fan, which is carefully designed and manufactured for your special needs by Dynatron Corporation.

2. ELECTRICAL CHARACTERISTICS

Items		Description		
1.	Rated Voltage	DC 12 V		
2.	Operating Voltage	12±10%		
3.	Start Voltage	7V		
4.	PWM 信號主頻 25KHz 幅度 5V	占空比 D= 0-20%	占空比 D= 50%	占空比 D= 100%
5.	Air Flow – At rated voltage zero static pressure (minimal value)	0.07m ³ /z min (2.453CFM)	0.164 m ³ / min (5.798CFM)	0.405m ³ / min (14.321CFM)
6.	Static Pressure – At rated voltage At zero air flow	1.252mm-H ₂ O (0.049inch-H ₂ O)	6.997mm-H ₂ O (0.275 inch-H ₂ O)	50.458mm-H ₂ O (1.986inch-H ₂ O)
7.	Input Current (Max.)	0.05A	0.1A	0.73A
8.	Speed (Max.)	1100RPM ±200	2600RPM ±10%	6000RPM ±10%
9.	Acoustical Noise	19.1dBA	34.2dBA	53.8dBA
10.	Input Power	0.6W	1.2W	8.76W
11.	Insulation Resistance – Between Frame and Terminal	10 M ohm at DC 500 V		
12.	Dielectric Strength – Between Frame and Terminal	5 mA (Max.) @ AC 500 V 60 Hz 1 min.		
13.	Life – Continuous operating under normal temperature (25 °C or 77 °F)	50,000 hours		
14.	Rotation	Clockwise Air Discharged		
15.	Autorestart Time	3-5sec		



DYNATRON CORPORATION

Dynaeon Industrial Co., Ltd.

16	Lead Wires	UL 1007, awg 28 or Equivalent “-”: Black; “+”: Yellow; “s”: Green. “PWM”: Blue
----	------------	---

3. MECHANICAL CHARACTERISTICS

Items		Description
1.	Dimension	Display as Drawing
2.	Frame	aluminium (GP)
3.	Impeller	PBT UL94V-0 (Black GP)
4.	Bearing System	Two ball Bearing
5.	Weight	77±5grams

4. ENVIRONMENTAL

Items		Description
1.	Operating Temperature	- 10 °C ~ + 65 °C (65 %RH)
2.	Storage Temperature	- 30 °C ~ + 70 °C (65 %RH)
3.	Vibration Test	Displacement Amplitude: 0.75mm(Equivalent 10G) Frequency Range:10Hz<->55Hz/30SEC. Linear Scanning 120 Cycle Endurance Timer Per Axis:30Min. Orientation:X,Y,Z.
4.	Drop Test	Motor withstands one free body drop from 30 cm in high onto 10 mm thickness of wooden board for each of the three faces in minimum packing condition.
5.	Acoustic Noise	19.1/34.2/53.8 dBA – Curve (Max dBA) Measuring Condition – Under rated voltage in semi-anechoic chamber equipment sound level meter. (Figure A.)



DYNATRON CORPORATION

Dynaeon Industrial Co., Ltd.




Figure A – Noise Level is measure at rated voltage in anechoic chamber in free air as above.

5. PROTECTION

Items		Description
1.	Polarity Protection	For polarity error connection to power, the circuit withstands reversed connection between positive and negative leads.
2.	Locked Rotor Protection	Motor winding protects the motor from damage in 72 hours of locked rotor condition at rated voltage.

ATTACHMENTS


- a. Assembly Drawing
- b. Product Dimension
- c. Electrical specifications for pwm production




DYNATRON CORPORATION

Dynaeon Industrial Co., Ltd.

ASSEMBLY




 DYNAEON INDUSTRIAL CO.,LTD.	DB127015BU-PWM		Tolerance		Approval	Chun Fu
			Unit	mm	Check	Shangwei Jiang
	Edition	1.0	Initiator	San shui		
	Drawing Type	Assembly	Remark		Date	2007/01/09



DYNATRON CORPORATION


Dynaeon Industrial Co., Ltd.

DIMENSIONS



UNIT:MM

LEAD WIRE:1007#26AWG 80°C 300V UL, CSA APPROVAL

 DYNAEON INDUSTRIAL CO.,LTD.	DB127015BU-PWM		Tolerance	Vide Supra	Approval	Chun Fu
			Unit	mm	Check	ShangWei Jiang
	Drawing Type		Dimensions	Remark	Date	2007/01/09



DYNATRON CORPORATION

Dynaeon Industrial Co., Ltd.

USA Dynatron Corp.

Electrical Specifications for PWM production

Voltage

Fan operating voltage shall be within the range 12V \pm 1.2V.

Current

Peak fan current draw during start-up operation(with 13.2V applied,with fan operating in the free stream condition)shall not exceed 2.0 A.

Fan current spike during start-up operation(with 13.2V applied with fan operating in the free stream condition)shall be allowed to exceed 1.0 A for a duration of no greater than 1.0 sec.

Tachometer Output Signal

Fan shall provide tachometer output signal with the following characteristics:

- * Two pulses per revolution
- * Open-collector or open-drain type output
- * Motherboard will have a pull up to 12V, maximum 13.2V

PWM Control Input Signal

The following requirements are measured at the PWM(control) pin of the fan cable

connector:PWM Frequency:Target frequency 25kHz,

acceptable operational range 21 kHz to 28 KHz

Maximum voltage for logic low:VIL=0.8V

Absolute maximum current sourced:Imax=5mA(short circuit current)

Absolute maximum voltage level:Vmax=5.25V(open circuit voltage)

Fan Speed Control

1.1Maximum Fan Speed Requirements

The maximum fan speed shall be specified for the fan model by the vendor and correspond to 100% duty cycle PWM signal input.

1.2 Minimum Fan Speed Requirements

The vendor shall specify the minimum RPM and the corresponding PWM duty cycle. This specified minimum RPM shall be 30% of maximum RPM or less.The fan shall be able to start and run at this RPM. To allow a lower specified minimum RPM,it is acceptable to provide a higher PWM duty cycle to the fan motor for a short period of time for startup conditions.This pulse should not exceed 30% maximum RPM and should last no longer than 2 seconds.



DYNATRON CORPORATION


Dynaeon Industrial Co., Ltd.

USA Dynatron Corp.

1.3 Fan Speed Response PWM Control Input Signal

The PWM input shall be delivered to the fan through the control signal on Pin4. Fan speed response to this signal shall be a continuous and monotonic of the duty cycle of the signal, from 100% to the minimum specified RPM. The fan RPM (as a percentage of maximum RPM) should match the PWM duty cycle within $\pm 10\%$. If no control signal is present the fan shall operate at maximum RPM.

Figure 1 Fan speed Response to PWM Control input Signal



1.4 Operation Below Minimum RPM

For all duty cycles less than the minimum duty cycle, the RPM shall not be greater than the minimum RPM. The following graphs and definitions show three recommended solutions to handle PWM duty cycles that are less than the minimum operational PWM, as a percentage of maximum.

Reference resource by Intel's 4-wire PWM Fan controlled specification.